

T.LUG[®]

ELECTRICAL TERMINALS

HIGH AND LOW VOLTAGE
ELECTRICAL TERMINALS

HTL 150-12
T.LUG

HTL 150-12
T.LUG

150 MM²
CU
CL 150-10
T.LUG

2013

MAKE THE PERFECT CONNECTION

CONTENTS

page
04., 05.
RING TERMINALS



page
10.
MALE DISCONNECTS



page
13.
QUICK SPLICES



page
05.
SQUARE TERMINALS



page
10.
FEMALE DISCONNECTS



page
14.
CORD-END SLEEVES



page
06.
INSULATED
RING TERMINALS



page
11.
FULLY INSULATED
FEMALE DISCONNECTOR



page
14.
CORD-END TWIN SLEEVES



page
06.
SPADE TERMINALS



page
11.
BULLET TERMINALS



page
15.
NON - INSULATED
CORD - END SLEEVES



page
06.
INSULATED
SPADE TERMINALS



page
11.
BULLET SOCKETS



page
16.
HIGH VOLTAGE ELECTRICAL
TERMINALS SHORT BARREL



page
07.
CABLE LUGS
CL TYPE



page
11.
INSULATED
PIN TERMINALS



page
17.
HIGH VOLTAGE ELECTRICAL
TERMINALS LONG BARREL



page
08.
CABLE LUGS
LCL TYPE



page
12.
FLAT BLADE
INSULATED TERMINALS



page
18.
HIGH VOLTAGE OBTUSE ANGLE
ELECTRICAL TERMINALS SHORT BARREL



page
09.
COPPER CRIMP SLEEVES



page
12.
CLOSED - END
CONNECTORS



page
19.
HIGH VOLTAGE OBTUSE ANGLE
ELECTRICAL TERMINALS LONG BARREL



page
09.
PARALLEL SPLICES



page
13.
ALL PLASTIC
CONNECTORS



page
20.
HIGH VOLTAGE 90° ELECTRICAL
TERMINALS SHORT BARREL



page
10.
BUTT SPLICES



page
13.
WIRE-NUT
CONNECTORS



page
21.
HIGH VOLTAGE 90° ELECTRICAL
TERMINALS LONG BARREL



page
10.
OPEN - BARREL
TERMINALS




page
13.
WIRE-NUT
CONNECTORS WRENCH



page
22.
HIGH VOLTAGE ELECTRICAL
SPLICE LONG BARREL




RING TERMINALS (R-TYPE) NON-INSULATED




Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]					AWG	DIN mm ²	Q'TY in box
		d2φ	B	L	Dφ	d1φ			
R 1.5-3	1.5	3.7	8.0	15.5	3.3	1.7	22-16	0.5-1.5	2,500
R 1.5-4		4.3							
R 1.5-5		5.3							
R 2.5-3	2.5	3.7	8.5	16.5	3.9	2.3	16-14	1.5-2.5	2,500
R 2.5-4		4.3							
R 2.5-5		5.3							
R 2.5-6		6.4							
R 4-4	4	4.3	8.8	18.4	5.0	3.0	14-12	2.5-4	2,000
R 4-5		5.3							
R 4-6		6.4							
R 6-4		4.3							
R 6-5	6	5.3	9.5	19.8	5.4	3.4	12-10	4-6	2,000
R 6-6		6.4							
R 6-8		8.4							
R 6-10		10.5							
R 10-6	10	6.4	12.0	23.8	6.9	4.5	8	10	1,000
R 10-8		8.4							
R 10-10		10.5							
R 16-6		6.4							
R 16-8	16	8.4	15.2	32.0	8.8	5.8	6	16	500
R 16-10		10.5							
R 25-6		6.4							
R 25-8	25	8.4	16.5	34.5	11.3	7.7	4	25	250
R 25-10		10.5							
R 25-12		13.0							
R 35-6	35	6.4	19.4	38.7	11.8	8.2	2	35	200
R 35-8		8.4							
R 35-10		10.5							
R 35-12		13.0							
R 50-8S	50	8.4	16.0	38.5	13.4	9.8	1/0	50	200
R 50-10S		10.5							
R 50-6		6.4							
R 50-8		8.4							
R 50-10	70	10.5	22.0	42.7	15.4	11.4	2/0	70	100
R 50-12		13.0							
R 70-8		8.4							
R 70-10		10.5							
R 70-12	95	13.0	24.0	51.5	17.5	13.5	4/0	95	100
R 95-6		6.4							
R 95-8		8.4							
R 95-10		10.5							
R 95-12	120	13.0	27.0	54.4	19.4	15.0	250 MCM	120	50
R 120-8		8.4							
R 120-10		10.5							
R 120-12		13.0							
R 120-14	150	13.0	32.0	68.0	22.0	16.8	250 - 300 MCM	150	50
R 120-16		15.0							
R 150-6		6.4							
R 150-8		8.4							
R 150-10	185	10.5	28.5	56.0	25.9	19.5	300 - 500 MCM	185	25
R 150-12		13.0							
R 185-12		13.0							
R 185-14		15.0							
R 185-16	185	17.0	36.0	67.5	25.9	19.5	300 - 500 MCM	185	25
R 185-18		19.0							
R 185-20		21.0							
R 185-22		23.0							

RING TERMINALS (R-TYPE) NON-INSULATED




Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]					AWG	DIN mm ²	Q'TY in box
		d2φ	B	L	Dφ	d1φ			
R 240-12	240	13.0	38.5	70.3	29.0	22.0	350-500 MCM	240	25
R 240-14		15.0							
R 240-16		17.0							
R 240-18		19.0							
R 240-20		21.0							
R 300-12	300	13.0	44.0	72.0	32.0	24.0	600 MCM	300	20
R 300-14		15.0							
R 300-16		17.0		91.0					
R 300-18		19.0							
R 300-20		21.0							
R 400-12	400	13.0	50.0	88.0	37.0	28.0	800 MCM	400	10
R 400-14		15.0							
R 400-16		17.0		105.5					
R 400-18		19.0							
R 400-20		21.0							

SQUARE TERMINALS (RS-TYPE) NON-INSULATED




Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]		AWG	DIN mm ²	Q'TY in box
		d2φ	B			
RS 50-6S	50	6.4	13.5	2	35-50	200
RS 50-8S		8.4				
RS 50-8		8.4	16.3			
RS 50-10		10.5				
RS 70-8	70	8.4	16.3	1/0-2/0	70	100
RS 70-10		10.5				
RS 95-8	95	8.4	19.3	4/0	95	100
RS 95-10		10.5				
RS 95-12		13.0				
RS 120-8	120	8.4	21.3	4/0-250 MCM	120	50
RS 120-10		10.5				
RS 120-12		13.0				
RS 150-8	150	8.4	22.3	250-300 MCM	150	50
RS 150-10		10.5				
RS 150-12		13.0				
RS 185-8	185	8.4	27.0	300-350 MCM	185	25
RS 185-10		10.5				
RS 185-12		13.0				
RS 240-10	240	10.5	28.5	350-500 MCM	240	25
RS 240-12		13.0				
RS 240-16		17.0				
RS 300-10	300	10.5	33.0	600 MCM	300	20
RS 300-12		13.0				
RS 300-16		17.0				
RS 400-12	400	13.0	37.0	750 MCM	400	10
RS 400-16		17.0				
RS 400-18		19.0				
RS 400-20		21.0				

INSULATED RING TERMINALS (RF-TYPE)




Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]						Color	AWG	DIN mm ²	Q'TY in box
		d2φ	B	L	L1	ℓ	d1φ				
RF 1.5-3	1.5	3.7	8.0	21.5	15.5	10.5	4.0	Red	22-16	0.5-1.5	2,000
RF 1.5-4		4.3									
RF 1.5-5		5.3									
RF 2.5-3	2.5	3.7	8.5	22.6	16.5	10.7	4.5	Blue	16-14	1.5-2.5	1,000
RF 2.5-4		4.3									
RF 2.5-5		5.3									
RF 2.5-6	4	6.4	12.0	28.5	22.4	13.5	6.0	Black	14-12	2.5-4	1,000
RF 4-4		4.3									
RF 4-5		5.3									
RF 4-6	6	6.4	12.0	32.5	26.1	13.5	6.5	Yellow	12-10	4-6	500
RF 6-4		4.3									
RF 6-5		5.3									
RF 6-6	6	6.4	12.0	32.5	26.1	13.5	6.5	Yellow	12-10	4-6	500
RF 6-8		8.4									
RF 6-10		10.5									

SPADE TERMINALS (Y-TYPE)




Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]					AWG	DIN mm ²	Q'TY in box
		d2φ	B	L	Dφ	d1φ			
Y 1.5-3S	1.5	3.3	5.7	16.0	3.3	1.7	22-16	0.5-1.5	2,500
Y 1.5-4S		4.3	6.4						
Y 1.5-5S		5.3	8.0						
Y 2.5-3S	2.5	3.3	5.7	16.0	3.9	2.3	16-14	1.5-2.5	2,500
Y 2.5-4S		4.3	6.4						
Y 2.5-5S		5.3	7.3						
Y 4-4	4	4.3	8.0	18.3	5.0	3.0	14-12	2.5-4	2,000
Y 4-5		5.3							
Y 6-4S		4.3	7.2	18.8	5.4	3.4	12-10	4-6	2,000
Y 6-5S	6	5.3	8.2						
Y 6-6		6.4	12.0						

INSULATED SPADE TERMINALS (YF-TYPE)



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]						Color	AWG	DIN mm ²	Q'TY in box
		d2φ	B	L	L1	ℓ	d1φ				
YF 1.5-3S	1.5	3.3	5.7	22.0	16.0	10.5	4.0	Red	22-16	0.5-1.5	2,000
YF 1.5-4S		4.3	6.4								
YF 1.5-5S		5.3	8.0								
YF 2.5-3S	2.5	3.3	5.7	22.0	16.0	10.7	4.5	Blue	16-14	1.5-2.5	1,000
YF 2.5-4S		4.3	6.4								
YF 2.5-5S		5.3	7.3								
YF 4-4	4	4.3	8.0	25.5	18.3	13.5	6.0	Black	14-12	2.5-4	1,000
YF 4-5		5.3									
YF 6-4S		4.3	7.2	25.5	18.8	13.5	6.5	Yellow	12-10	4-6	500
YF 6-5S	6	5.3	8.2								
YF 6-6		6.4	12.0								

CABLE LUGS (CL TYPE COPPER TUBE)




LISTED

WIRE CONNECTOR
3LDJ
FILE No: E304648

Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]							AWG	DIN mm ²	Q'TY in box
		d2φ	d1φ	Dφ	B	E	F	L			
CL 10-6	10	6.4	4.5	6.2	10.0	9.0	10.0	25.0	8	10	1,000
CL 10-8		8.4			12.6						
CL 16-6	16	6.4	5.4	7.1	10.0	12.0	11.0	30.0	6	16	500
CL 16-8		8.4			12.6						
CL 25-6	25	6.4	6.8	8.8	12.6	12.0	11.0	30.0	4	25	400
CL 25-8		8.4			15.0			31.0			
CL 25-10		10.5									
CL 35-6	35	6.4	8.2	10.6	15.0	12.0	14.0	35.0	2	35	300
CL 35-8		8.4			18.6						
CL 35-10		10.5									
CL 35-12		13.0									
CL 50-8	50	8.4	9.5	12.4	18.0	16.0	17.0	43.0	1/0	50	200
CL 50-10		10.5			19.0						
CL 50-12		13.0									
CL 70-8	70	8.4	11.2	14.7	21.0	18.0	20.0	50.0	2/0	70	100
CL 70-10		10.5									
CL 70-12		13.0									
CL 95-8	95	8.4	13.5	17.4	25.5	20.0	22.0	55.0	4/0	95	80
CL 95-10		10.5									
CL 95-12		13.0									
CL 120-10	120	10.5	15.0	19.4	28.0	22.0	24.0	60.0	250 MCM	120	50
CL 120-12		13.0									
CL 120-14		15.0									
CL 120-16		17.0									
CL 150-10	150	10.5	16.5	21.2	30.5	26.0	27.0	69.0	300 MCM	150	50
CL 150-12		13.0									
CL 150-14		15.0									
CL 150-16		17.0									
CL 185-12	185	13.0	18.5	23.5	34.0	32.0	29.0	78.0	350 MCM	185	32
CL 185-14		15.0									
CL 185-16		17.0									
CL 240-12	240	13.0	21.5	27.0	39.5	39.5	34.0	92.0	500 MCM	240	20
CL 240-14		15.0									
CL 240-16		17.0									
CL 300-12	300	13.0	23.5	30.0	43.5	42.0	37.0	101.0	600 MCM	300	15
CL 300-14		15.0									
CL 300-16		17.0									
CL 300-18		19.0									
CL 400-14	400	15.0	27.0	35.0	50.8	50.8	44.0	114.0	800 MCM	400	7
CL 400-16		17.0									
CL 400-18		19.0									
CL 400-20		21.0									
CL 500-12	500	13.0	30.0	39.0	56.0	48.0	48.0	124.0	1000 MCM	500	5
CL 500-16		17.0									
CL 500-18		19.0									
CL 500-20		21.0									

CABLE LUGS (LCL TYPE COPPER TUBE)



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]							AWG	DIN mm ²	Q'TY in box	
		d2φ	d1φ	Dφ	B	E	F	L				
LCL 10-6	10	6.4	4.5	6.2	10.0	11.0	10.0	27.0	8	10	1,000	
LCL 10-8		8.4			12.6							
LCL 16-6	16	6.4	5.4	7.1	10.0	14.0	11.0	32.0	6	16	500	
LCL 16-8		8.4			12.6							
LCL 25-6	25	6.4	6.8	8.8	12.6	14.0	11.0	32.0	4	25	400	
LCL 25-8		8.4			15.0			33.0				
LCL 25-10	35	10.5	8.2	10.6		15.0	14.0		14.0	37.0	2	35
LCL 35-6		6.4										
LCL 35-8		8.4										
LCL 35-10		10.5										
LCL 35-12	50	13.0	9.5	12.4	18.0	21.0	17.0	48.0	1/0	50	200	
LCL 50-8		8.4										19.0
LCL 50-10		10.5										
LCL 50-12		13.0										
LCL 70-8	70	8.4	11.2	14.7	21.0	25.0	20.0	57.0	2/0	70	100	
LCL 70-10		10.5										
LCL 70-12		13.0										
LCL 95-8	95	8.4	13.5	17.4	25.5	30.0	22.0	65.0	4/0	95	80	
LCL 95-10		10.5										
LCL 95-12		13.0										
LCL 120-10	120	10.5	15.0	19.4	28.0	30.0	24.0	68.0	250 MCM	120	50	
LCL 120-12		13.0										
LCL 120-14		15.0										
LCL 120-16		17.0										
LCL 150-10	150	10.5	16.5	21.2	30.5	35.0	27.0	78.0	300 MCM	150	50	
LCL 150-12		13.0										
LCL 150-14		15.0										
LCL 150-16		17.0										
LCL 185-12	185	13.0	18.5	23.5	34.0	40.0	29.0	86.0	350 MCM	185	32	
LCL 185-14		15.0										
LCL 185-16		17.0										
LCL 240-12	240	13.0	21.5	27.0	39.5	45.0	34.0	99.0	500 MCM	240	20	
LCL 240-14		15.0										
LCL 240-16		17.0										
LCL 300-12	300	13.0	23.5	30.0	43.5	50.0	37.0	109.0	600 MCM	300	15	
LCL 300-14		15.0										
LCL 300-16		17.0										
LCL 300-18		19.0										
LCL 400-14	400	15.0	27.0	35.0	50.8	55.0	44.0	125.0	800 MCM	400	7	
LCL 400-16		17.0										
LCL 400-18		19.0										
LCL 400-20		21.0										
LCL 500-12	500	13.0	30.0	39.0	56.0	60.0	48.0	136.0	1000 MCM	500	5	
LCL 500-16		17.0										
LCL 500-18		19.0										
LCL 500-20		21.0										


* Special ordered only

COPPER CRIMP SLEEVES (CSL-TYPE)



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]			AWG	DIN mm ²	Q'TY in box
		d1φ	Dφ	L			
CSL 10	10	4.5	6.2	25.0	8	10	700
CSL 16	16	5.4	7.1	33.0	6	16	500
CSL 25	25	6.8	8.8	33.0	4	25	300
CSL 35	35	8.2	10.6	38.0	2	35	200
CSL 50	50	9.5	12.4	46.0	1/0	50	160
CSL 70	70	11.2	14.7	53.0	2/0	70	100
CSL 95	95	13.5	17.4	58.0	4/0	95	60
CSL 120	120	15.0	19.4	63.0	250 MCM	120	50
CSL 150	150	16.5	21.2	72.0	300 MCM	150	35
CSL 185	185	18.5	23.5	82.0	350 MCM	185	25
CSL 240	240	21.5	27.0	96.0	500 MCM	240	20
CSL 300	300	23.5	30.0	105.0	600 MCM	300	12
CSL 400	400	27.0	35.0	105.0	800 MCM	400	8
CSL 500	500	30.0	39.0	105.0	1000 MCM	500	7

PARALLEL SPLICES (P-TYPE)



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]			AWG	DIN mm ²	Q'TY in box
		d1φ	Dφ	L			
P 10	10	4.5	6.2	9.5	8	10	1,000
P 16	16	5.4	7.1	11.0	6	16	1,000
P 25	25	6.8	8.8	13.5	4	25	500
P 35	35	8.2	10.6	15.0	2	35	500
P 50	50	9.5	12.4	16.5	1/0	50	300
P 70	70	11.2	14.7	18.5	2/0	70	200
P 95	95	13.5	17.4	19.0	4/0	95	100
P 120	120	15.0	19.4	19.5	250 MCM	120	80
P 150	150	16.5	21.2	20.0	300 MCM	150	50
P 185	185	18.5	23.5	27.0	350 MCM	185	50
P 240	240	21.5	27.0	28.5	500 MCM	240	30
P 300	300	23.5	30.0	32.0	600 MCM	300	20
P 400	400	27.0	35.0	37.0	800 MCM	400	10
P 500	500	30.0	39.0	40.0	1000 MCM	500	10

*Special ordered only

BUTT SPLICES



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]		AWG	DIN mm ²	Q'TY in box
			d1φ	L			
BF 1.5	1.5	● Red	4.0	25.0	22-16	0.5-1.5	1,000
BF 2.5	2.5	● Blue	4.5	27.0	16-14	1.5-2.5	1,000
BF 6	6	● Yellow	6.5	27.0	12-10	4-6	500


OPEN-BARREL TERMINALS



Item No.	Tab Size	Q'TY in box	Q'TY in roll
MMF-1	.250 x .032" 6.35 x 0.8mm.	1,000	-
M-250K	.250 x .032" 6.35 x 0.8mm.	1,000	5,000
K-305	.250 x .032" 6.35 x 0.8mm.	1,000	5,000
FL 1-7A	.250 x .032" 6.35 x 0.8mm.	1,000	-


* Special ordered only

MALE DISCONNECTS




Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
			B	L	L1	d1φ			
V1.5-7B	.250X.032" 6.35x0.8mm.	● Red	6.3	21.0	11.0	3.3	22-16	0.5-1.5	1,000
V2.5-7B		● Blue	6.3	21.0	11.0	4.0	16-14	1.5-2.5	1,000
V6-7B		● Yellow	6.3	23.0	11.0	5.5	12-10	4-6	500

FEMALE DISCONNECTS



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
			B	L	L1	d1φ			
V1.5-7A	.250X.032" 6.35x0.8mm.	● Red	6.5	21.0	11.0	3.3	22-16	0.5-1.5	1,000
V2.5-7A		● Blue	6.5	21.0	11.0	4.0	16-14	1.5-2.5	1,000
V6-7A		● Yellow	6.5	23.0	11.0	5.5	12-10	4-6	500

FULLY INSULATED FEMALE DISCONNECTOR




Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
			B	L	L1	d1φ			
PV 1.5-7A	.250X.032" 6.35x0.8mm	Red	6.5	23.0	16.5	3.3	22-16	0.5-1.5	500
PV 2.5-7A		Blue	6.5	23.0	16.5	4.0	16-14	1.5-2.5	500
PV 6-7A		Yellow	6.5	23.0	16.5	5.5	12-10	4-6	500

BULLET TERMINALS




Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
			B	L	L1	d1φ			
F 1.5 B	1.5	Red	4.0	21.0	11.0	3.3	22-16	0.5-1.5	1,000
F 2.5 B	2.5	Blue	5.0	21.0	11.0	4.0	16-14	1.5-2.5	1,000
F 6 B	6	Yellow	5.0	21.0	11.0	5.5	12-10	4-6	500

BULLET SOCKETS




Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
			B	L	L1	d1φ			
F 1.5 A	1.5	Red	3.9	23.0	16.5	3.3	22-16	0.5-1.5	500
F 2.5 A	2.5	Blue	4.9	23.0	16.5	4.0	16-14	1.5-2.5	500
F 6 A	6	Yellow	4.9	23.0	16.5	5.5	12-10	4-6	500

INSULATED PIN TERMINALS




Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]			AWG	DIN mm ²	Q'TY in box
			Bφ	L	L1			
PIN 1.5 AF	1.5	Red	1.9	22.0	12.5	22-16	0.5-1.5	1,000
PIN 2.5 AF	2.5	Blue	1.9	22.0	12.5	16-14	1.5-2.5	1,000
PIN 6 AF	6	Yellow	2.7	27.5	13.5	12-10	4-6	500

FLAT BLADE INSULATED TERMINALS



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]			AWG	DIN mm ²	Q'TY in box
			B	L	L1			
PIN 110 FB	1.5	● Red	2.3	20.0	10.0	22-16	0.5-1.5	1,000
PIN 210 FB	2.5	● Blue	2.3	20.0	10.0	16-14	1.5-2.5	1,000
PIN 510 FB	6	● Yellow	2.8	23.0	10.0	12-10	4-6	500

FLAT BLADE INSULATED TERMINALS



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]			AWG	DIN mm ²	Q'TY in box
			B	L	L1			
PIN 118 FB	1.5	● Red	2.3	28.0	18.0	22-16	0.5-1.5	1,000
PIN 218 FB	2.5	● Blue	2.3	28.0	18.0	16-14	1.5-2.5	1,000
PIN 518 FB	6	● Yellow	3.0	31.0	18.0	12-10	4-6	500

CLOSED-END CONNECTORS



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]	AWG	DIN mm ²	Q'TY in box
			L			
N 1.5	0.5-1.5	Clear	18.1	22-16	0.5-1.5	1,000
N 2.5	1.5-2.5		20.1	16-14	1.5-2.5	500
N 6	4-6		25.5	12-10	4-6	250
N 10	10		27.5	8	10	250

CLOSED-END CONNECTORS



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]	AWG	DIN mm ²	Q'TY in box
			L			
NO. 22	0.5-1.5	● Blue	18.1	22-16	0.5-1.5	1,000
NO. 33	1.5-2.5	● Orange	20.1	16-14	1.5-2.5	500
NO. 44	4-6	● Yellow	25.5	12-10	4-6	250
NO. 66	10	● Red	27.5	8	10	250

ALL PLASTIC CONNECTORS

(วายนัทพลาสติก)



Item No.	TIS Wire Size mm ²	Color	AWG	DIN mm ²	Q'TY in box
U1-11	0.5-1.5	● Yellow	22-16	0.5-1.5	1,000
U2-22	0.5-2.5	● Ivory	22-14	0.5-2.5	500
U3-33	0.5-2.5	● Ivory	22-14	0.5-2.5	400

WIRE - NUT CONNECTORS

(วายนัท สปริงเหล็ก)



Inner assembled with square spring steel wires.

ชุดลวดสปริงภายในเป็นเส้นเหล็ก ช่วยล็อกและรัดสายให้แน่นขึ้น



Item No.	TIS Wire Size mm ²	Color	AWG	DIN mm ²	Q'TY in box
P1 - 11	0.5-1.5	● Gray	22-16	0.5-1.5	1,000
P2 - 22	0.5-2.5	● Blue	22-14	0.5-2.5	500
P3 - 33	0.5-2.5	● Orange	22-14	0.5-2.5	400
P4 - 44	1-4	● Yellow	18-12	1-4	250
P6 - 66	1-6	● Red	18-10	1-6	200

WIRE - NUT CONNECTORS WRENCH

(ไขควงวายนัท)



ช่วยในการหมุนวายนัทให้ง่ายขึ้น



Item No.	Color	Q'TY in Pack
H - 2004	● Orange	1

For Wire-Nut P2-22, P3-33, P4-44, P6-66

QUICK SPLICES

(ตลับหนีบสาย)




วิธีการต่อสายไฟ




Item No.	TIS Wire Size mm ²	Color	AWG	DIN mm ²	Q'TY in box
SS 1.5	1.5	● Red	22-16	0.5-1.5	200
SS 2.5	2.5	● Blue	16-14	1.5-2.5	200
SS 4	6	● Yellow	12-10	4-6	100

CORD-END SLEEVES




Item No.	TIS Wire Size mm	Color			DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
		(T)French	(W)German	(D)Din	A	B	Cø	Dø			
CE 0.5-6	0.5	○ White	● Orange	○ White	12.0	6.0	1.3	3.2	22	0.5	2,000
CE 0.5-8					14.0	8.0					
CE 0.5-10					16.0	10.0					
CE 0.75-6	0.75	● M.blue	○ White	● Gray	12.0	6.0	1.5	3.4	20	0.75	2,000
CE 0.75-8					14.0	8.0					
CE 0.75-10					16.0	10.0					
CE 0.75-12	1	● Red	● Yellow	● Red	18.0	12.0	1.7	3.6	18	1	2,000
CE 1.0-6					12.0	6.0					
CE 1.0-8					14.0	8.0					
CE 1.0-10	1.5	● Black	● d.red	● Black	16.0	10.0	2.0	4.1	16	1.5	2,000
CE 1.0-12					18.0	12.0					
CE 1.5-8					14.0	8.0					
CE 1.5-10	2.5	● Gray	● Blue	● Blue	16.0	10.0	2.5	4.8	14	2.5	2,000
CE 1.5-12					18.0	12.0					
CE 2.5-8					14.0	8.0					
CE 2.5-10	4	● Orange	● Gray	● Gray	16.0	10.0	3.2	5.5	12	4	2,000
CE 2.5-12					18.0	12.0					
CE 4.0-10					17.0	10.0					
CE 4.0-12	6	● Green	● Black	● Yellow	20.0	12.0	3.9	7.0	10	6	1,000
CE 4.0-18					26.0	18.0					
CE 6.0-12					20.0	12.0					
CE 6.0-18	10	● Brown	● Ivory	● Red	26.0	18.0	4.9	8.4	8	10	500
CE 10-12					22.0	12.0					
CE 10-18					28.0	18.0					
CE 16-12	16	● Ivory	● Green	● Blue	24.0	12.0	6.2	9.6	6	16	500
CE 16-18					28.0	18.0					
CE 25-16					28.0	16.0					
CE 25-22	25	● Black	● Brown	● Yellow	35.0	22.0	7.7	12.0	4	25	200
CE 35-16					30.0	16.0					
CE 35-25					39.0	25.0					
CE 50-20	50	● Blue	● Olive	● Blue	36.0	20.0	10.9	16.0	1/0	50	100
CE 50-25					40.0	25.0					

CORD-END TWIN SLEEVES



Item No.	TIS Wire Size mm ²	Color	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
			A	B	Cø	D			
CE 0.75-8X2	0.75	● Gray	15.0	8.0	2.1	5.5	20	0.75	1,000
CE 1.0-8X2	1	● Red	15.0	8.0	2.35	6.0	18	1	1,000
CE 1.5-8X2	1.5	● Black	16.0	8.0	2.6	7.2	16	1.5	1,000
CE 2.5-10X2	2.5	● Blue	18.5	10.0	3.2	8.4	14	2.5	1,000


NON - INSULATED CORD-END SLEEVES



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]				AWG	DIN mm ²	Q'TY in box
		L	d1φ	D1φ	D2φ			
CN 0.5-6	0.5	6.0	1.0	1.3	2.1	22	0.5	2,000
CN 0.5-8		8.0						
CN 0.5-10		10.0						
CN 0.75-6	0.75	6.0	1.2	1.5	2.3	20	0.75	2,000
CN 0.75-8		8.0						
CN 0.75-10		10.0						
CN 0.75-12		12.0						
CN 1.0-6	1	6.0	1.4	1.7	2.5	18	1	2,000
CN 1.0-8		8.0						
CN 1.0-10		10.0						
CN 1.0-12		12.0						
CN 1.5-8	1.5	8.0	1.7	2.0	2.8	16	1.5	2,000
CN 1.5-10		10.0						
CN 1.5-12		12.0						
CN 2.5-8	2.5	8.0	2.2	2.5	3.4	14	2.5	2,000
CN 2.5-10		10.0						
CN 2.5-12		12.0						
CN 4.0-10	4	10.0	2.8	3.2	4.0	12	4	2,000
CN 4.0-12		12.0						
CN 4.0-18		18.0						
CN 6.0-12	6	12.0	3.5	3.9	4.7	10	6	2,000
CN 6.0-18		18.0						
CN 10-12	10	12.0	4.5	4.9	5.8	8	10	1,000
CN 10-18		18.0						
CN 16-12	16	12.0	5.8	6.2	7.5	6	16	1,000
CN 16-18		18.0						
CN 25-16	25	16.0	7.3	7.7	9.5	4	25	500
CN 25-22		22.0						
CN 35-16	35	16.0	8.3	8.7	11.0	2	35	400
CN 35-25		25.0						
CN 50-20	50	20.0	10.3	10.9	13.0	1/0	50	200
CN 50-25		25.0						
CN 70-22	70	22.0	13.5	14.3	15.3	2/0	70	50
CN 70-25		25.0						
CN 95-25	95	25.0	14.7	15.5	16.6	3/0	95	40
CN 95-32		32.0						
CN 120-30	120	30.0	16.7	17.6	18.6	4/0	120	25
CN 120-32		32.0						
CN 120-34		34.0						
CN 150-32	150	32.0	19.5	20.5	21.5	250-300 MCM	150	25
CN 150-38		38.0						

HIGH VOLTAGE ELECTRICAL TERMINALS SHORT BARREL ONE HOLE (HTS TYPE, หัวปลากลึงสูงชนิดรูเดียว)


Has provide machanical strength for heavy duty applications. Suitable for use with cable size from 10-500 SQ.MM. 12-35 KV.



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]									Q'TY in box
		d2φ	d1φ	Dφ	A	B	E	F	H	L	
HTS 10-6	10	6.4	4.5	6.2	9.5	12.0	21.5	7.4	11.5	49.9	100
HTS 10-8		8.4									
HTS 16-6	16	6.4	5.4	7.1	9.5	12.0	25.0	7.4	11.5	53.4	100
HTS 16-8		8.4									
HTS 25-6	25	6.4	6.8	8.8	11.5	15.0	28.5	7.4	13.5	60.9	100
HTS 25-8		8.4									
HTS 25-10		10.5									
HTS 35-6	35	6.4	8.2	10.6	11.5	17.0	32.0	8.0	13.5	65.0	50
HTS 35-8		8.4									
HTS 35-10		10.5									
HTS 50-8	50	8.4	9.5	12.4	13.5	19.0	35.0	10.9	15.5	74.9	40
HTS 50-10		10.5									
HTS 50-12		13.0									
HTS 70-8	70	8.4	11.2	14.7	13.5	21.0	35.0	10.9	17.5	76.9	40
HTS 70-10		10.5									
HTS 70-12		13.0									
HTS 95-8	95	8.4	13.5	17.4	13.5	25.5	38.0	15.8	17.5	84.8	20
HTS 95-10		10.5									
HTS 95-12		13.0									
HTS 120-10	120	10.5	15.0	19.4	14.5	28.0	40.0	18.8	18.5	91.8	20
HTS 120-12		13.0									
HTS 120-14		15.0									
HTS 150-12	150	13.0	16.5	21.2	16.5	30.5	50.0	19.8	20.5	106.8	20
HTS 150-14		15.0									
HTS 150-16		17.0									
HTS 185-12	185	13.0	18.5	23.5	16.5	34.0	50.0	19.8	20.5	106.8	10
HTS 185-14		15.0									
HTS 185-16		17.0									
HTS 240-12	240	13.0	21.5	27.0	16.5	39.5	56.0	24.8	20.5	117.8	10
HTS 240-14		15.0									
HTS 240-16		17.0									
HTS 300-12	300	13.0	23.5	30.0	20.0	43.5	67.0	26.8	24.0	137.8	10
HTS 300-14		15.0									
HTS 300-16		17.0									
HTS 400-12	400	13.0	27.0	35.0	23.0	50.8	67.0	26.8	27.0	143.8	5
HTS 400-14		15.0									
HTS 400-16		17.0									
HTS 500-12	500	13.0	30.0	39.0	23.0	56.0	75.0	33.8	27.0	158.8	5
HTS 500-14		15.0									
HTS 500-16		17.0									

HIGH VOLTAGE ELECTRICAL TERMINALS LONG BARREL TWO HOLES (HTL TYPE, ทาวปลาแรงสูงชนิดรูคู่)


Permitted crimp in larger size for additional assurance on heavy duty load suitable for terminating cable size from 10-500 SQ.MM. 12-35 KV.



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]										Q'TY in box
		d2φ	d1φ	Dφ	A	B	C	E	F	H	L	
HTL 10-6	10	6.4	4.5	6.2	9.5	12.0	15.8	21.5	7.4	11.5	65.7	100
HTL 10-8		8.4										
HTL 16-6	16	6.4	5.4	7.1	9.5	12.0	15.8	25.0	7.4	11.5	69.2	100
HTL 16-8		8.4										
HTL 25-6	25	6.4										
HTL 25-8		8.4	6.8	8.8	11.5	15.0	15.8	28.5	7.4	13.5	76.7	100
HTL 25-10		10.5										
HTL 35-6	35	6.4										
HTL 35-8		8.4	8.2	10.6	11.5	17.0	19.0	32.0	8.0	13.5	84.0	50
HTL 35-10		10.5										
HTL 50-8	50	8.4										
HTL 50-10		10.5	9.5	12.4	11.5	19.0	22.7	35.0	10.9	13.5	93.6	40
HTL 50-12		13.0			13.5		44.4			15.5	119.3	
HTL 70-8	70	8.4										
HTL 70-10		10.5	11.2	14.7	11.5	21.0	22.7	35.0	10.9	13.5	93.6	40
HTL 70-12		13.0			13.5		44.4			17.5	121.3	
HTL 95-8	95	8.4										
HTL 95-10		13.5	10.5	17.4	13.5	25.5	44.4	38.0	15.8	17.5	129.2	20
HTL 95-12		13.0										
HTL 120-10	120	10.5										
HTL 120-12		13.0	15.0	19.4	14.5	28.0	44.4	40.0	18.8	18.5	136.2	20
HTL 120-14		15.0										
HTL 150-12	150	13.0										
HTL 150-14		15.0	16.5	21.2	16.5	30.5	44.4	50.0	19.8	20.5	151.2	20
HTL 150-16		17.0										
HTL 185-12	185	13.0										
HTL 185-14		15.0	18.5	23.5	16.5	34.0	44.4	50.0	19.8	20.5	151.2	10
HTL 185-16		17.0										
HTL 240-12	240	13.0										
HTL 240-14		15.0	21.5	27.0	16.5	39.5	44.4	56.0	24.8	20.5	162.2	10
HTL 240-16		17.0										
HTL 300-12	300	13.0										
HTL 300-14		15.0	23.5	30.0	16.5	43.5	44.4	67.0	26.8	20.5	175.2	10
HTL 300-16		17.0										
HTL 400-12	400	13.0										
HTL 400-14		15.0	27.0	35.0	16.5	50.8	44.4	67.0	26.8	20.5	175.2	5
HTL 400-16		17.0										
HTL 500-12	500	13.0										
HTL 500-14		15.0	30.0	39.0	16.5	56.0	44.4	75.0	33.8	20.5	190.2	5
HTL 500-16		17.0										

HIGH VOLTAGE OBTUSE ANGLE ELECTRICAL TERMINALS SHORT BARREL ONE HOLE (HOS TYPE, ทำมุมปลายแรงสูงชนิดรูเดียว 135°)


Suitable for use with cable size from
10-300 SQ.MM. in 135° angle position



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]												QTY in box
		d2φ	d1φ	Dφ	A	B	E	F	H	L	M	N	T	
HOS 10-6	10	6.4	4.5	6.2	9.5	12.0	21.5	7.4	16.5	26.0	50.8	21.5	1.1	100
HOS 10-8		8.4												
HOS 16-6	16	6.4	5.4	7.1	9.5	12.0	25.0	7.4	16.5	26.0	53.9	24.1	1.2	100
HOS 16-8		8.4												
HOS 25-6	25	6.4	6.8	8.8	11.5	15.0	28.5	7.4	18.5	30.0	61.6	27.0	1.6	100
HOS 25-8		8.4												
HOS 25-10		10.5												
HOS 35-6	35	6.4	8.2	10.6	11.5	17.0	32.0	8.0	21.5	33.0	68.8	30.3	2.0	50
HOS 35-8		8.4												
HOS 35-10		10.5												
HOS 50-8	50	8.4	9.5	12.4	13.5	19.0	35.0	10.9	23.5	37.0	78.2	35.0	2.5	40
HOS 50-10		10.5												
HOS 50-12		13.0												
HOS 70-8	70	8.4	11.2	14.7	13.5	21.0	35.0	10.9	27.5	41.0	83.8	36.0	3.5	40
HOS 70-10		10.5												
HOS 70-12		13.0												
HOS 95-8	95	8.4	13.5	17.4	13.5	25.5	38.0	15.8	27.5	41.0	91.3	41.6	3.6	20
HOS 95-10		10.5												
HOS 95-12		13.0												
HOS 120-10	120	10.5	15.0	19.4	14.5	28.0	40.0	18.8	28.5	43.0	98.3	45.9	4.3	20
HOS 120-12		13.0												
HOS 120-14		15.0												
HOS 150-12	150	13.0	16.5	21.2	16.5	30.5	50.0	19.8	30.5	47.0	111.3	53.8	4.5	10
HOS 150-14		15.0												
HOS 150-16		17.0												
HOS 185-12	185	13.0	18.5	23.5	16.5	34.0	50.0	19.8	30.5	47.0	113.0	54.1	4.8	5
HOS 185-14		15.0												
HOS 185-16		17.0												
HOS 240-12	240	13.0	21.0	27.0	16.5	39.5	56.0	24.8	35.5	52.0	127.9	62.6	5.5	5
HOS 240-14		15.0												
HOS 240-16		17.0												
HOS 300-12	300	13.0	23.5	30.0	20.0	43.5	67.0	26.8	44.0	64.0	151.5	72.6	6.3	5
HOS 300-14		15.0												
HOS 300-16		17.0												
HOS 400-12	400	13.0	27.0	35.0	23.0	50.8	67.0	26.8	47.0	70.0	155.9	74.2	7.9	1
HOS 400-14		15.0												
HOS 400-16		17.0												
HOS 500-12	500	13.0	30.0	39.0	23.0	56.0	75.0	33.8	47.0	70.0	169.9	85.8	8.9	1
HOS 500-14		15.0												
HOS 500-16		17.0												

HIGH VOLTAGE OBTUSE ANGLE ELECTRICAL TERMINALS LONG BARREL TWO HOLES (HOL TYPE, ทำมุมโค้งสูงชนิดรูคู่ 135°)


Suitable for use with cable size from
10- 500 SQ.MM. in 135° angle position



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]													Q'TY in box
		d2ø	d1ø	Dø	A	B	C	E	F	H	L	M	N	T	
HOL 10-6	10	6.4	4.5	6.2	9.5	12.0	15.8	21.5	7.4	16.5	41.8	66.6	21.5	1.1	100
HOL 10-8		8.4													
HOL 16-6	16	6.4	5.4	7.1	9.5	12.0	15.8	25.0	7.4	16.5	41.8	69.7	24.1	1.2	100
HOL 16-8		8.4													
HOL 25-6	25	6.4	6.8	8.8	11.5	15.0	15.8	28.5	7.4	18.5	45.8	77.4	27.0	1.6	100
HOL 25-8		8.4													
HOL 25-10		10.5													
HOL 35-6	35	6.4	8.2	10.6	11.5	17.0	19.0	32.0	8.0	21.5	52.0	87.8	30.3	2.0	50
HOL 35-8		8.4													
HOL 35-10		10.5													
HOL 50-8	50	8.4	9.5	12.4	11.5	19.0	22.7	35.0	10.9	21.5	55.7	96.9	35.0	2.5	40
HOL 50-10		10.5													
HOL 50-12		13.0													
HOL 70-8	70	8.4	11.2	14.7	11.5	21.0	22.7	35.0	10.9	23.5	57.7	100.6	36.0	3.5	40
HOL 70-10		10.5													
HOL 70-12		13.0													
HOL 95-8	95	8.4	13.5	17.4	13.5	25.5	44.4	38.0	15.8	27.5	85.4	135.7	41.6	3.6	20
HOL 95-10		10.5													
HOL 95-12		13.0													
HOL 120-10	120	10.5	15.0	19.4	14.5	28.0	44.4	40.0	18.8	28.5	87.4	142.7	45.9	4.3	10
HOL 120-12		13.0													
HOL 120-14		15.0													
HOL 150-12	150	13.0	16.5	21.2	16.5	30.5	44.4	50.0	19.8	30.5	91.4	155.7	53.8	4.5	10
HOL 150-14		15.0													
HOL 150-16		17.0													
HOL 185-12	185	13.0	18.5	23.5	16.5	34.0	44.4	50.0	19.8	30.5	91.4	157.4	54.1	4.8	4
HOL 185-14		15.0													
HOL 185-16		17.0													
HOL 240-12	240	13.0	21.5	27.0	16.5	39.5	44.4	56.0	24.8	35.5	96.4	172.3	62.6	5.5	4
HOL 240-14		15.0													
HOL 240-16		17.0													
HOL 300-12	300	13.0	23.5	30.0	16.5	43.5	44.4	67.0	26.8	40.5	101.4	188.9	72.6	6.3	2
HOL 300-14		15.0													
HOL 300-16		17.0													
HOL 400-12	400	13.0	27.0	35.0	16.5	50.8	44.4	67.0	26.8	40.5	101.4	193.5	74.2	7.9	1
HOL 400-14		15.0													
HOL 400-16		17.0													
HOL 500-12	500	13.0	30.0	39.0	16.5	56.0	44.4	75.0	33.8	40.5	101.4	205.9	85.8	8.9	1
HOL 500-14		15.0													
HOL 500-16		17.0													

HIGH VOLTAGE 90° ELECTRICAL TERMINALS SHORT BARREL ONE HOLE (HRS TYPE, ทางปลากล่องสูงชนิดรูเดียว 90°)


Suitable for use with cable size from
10-500 SQ.MM. in right angle position



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]												Q'TY in box
		d2φ	d1φ	Dφ	A	B	E	F	H	L	M	N	T	
HRS 10-6	10	6.4	4.5	6.2	9.5	12.0	21.5	7.4	16.5	26.0	32.2	29.5	1.1	100
HRS 10-8		8.4												
HRS 16-6	16	6.4	5.4	7.1	9.5	12.0	25.0	7.4	16.5	26.0	33.1	33.0	1.2	100
HRS 16-8		8.4												
HRS 25-6	25	6.4	6.8	8.8	11.5	15.0	28.5	7.4	18.5	30.0	38.8	36.7	1.6	100
HRS 25-8		8.4												
HRS 25-10		10.5												
HRS 35-6	35	6.4	8.2	10.6	11.5	17.0	32.0	8.0	21.5	33.0	43.6	41.0	2.0	50
HRS 35-8		8.4												
HRS 35-10		10.5												
HRS 50-8	50	8.4	9.5	12.4	13.5	19.0	35.0	10.9	23.5	37.0	49.4	47.2	2.5	40
HRS 50-10		10.5												
HRS 50-12		13.0												
HRS 70-8	70	8.4	11.2	14.7	13.5	21.0	35.0	10.9	27.5	41.0	55.7	47.7	3.5	40
HRS 70-10		10.5												
HRS 70-12		13.0												
HRS 95-8	95	8.4	13.5	17.4	13.5	25.5	38.0	15.8	27.5	41.0	58.4	55.6	3.6	20
HRS 95-10		10.5												
HRS 95-12		13.0												
HRS 120-10	120	10.5	15.0	19.4	14.5	28.0	40.0	18.8	28.5	43.0	62.4	61.0	4.3	20
HRS 120-12		13.0												
HRS 120-14		15.0												
HRS 150-12	150	13.0	16.5	21.2	16.5	30.5	50.0	19.8	30.5	47.0	68.2	72.1	4.5	10
HRS 150-14		15.0												
HRS 150-16		17.0												
HRS 185-12	185	13.0	18.5	23.5	16.5	34.0	50.0	19.8	30.5	47.0	70.5	72.2	4.8	5
HRS 185-14		15.0												
HRS 185-16		17.0												
HRS 240-12	240	13.0	21.5	27.0	16.5	39.5	56.0	24.8	35.5	52.0	79.0	83.6	5.5	5
HRS 240-14		15.0												
HRS 240-16		17.0												
HRS 300-12	300	13.0	23.5	30.0	20.0	43.5	67.0	26.8	44.0	64.0	94.0	97.0	6.3	5
HRS 300-14		15.0												
HRS 300-16		17.0												
HRS 400-12	400	13.0	27.0	35.0	23.0	50.8	67.0	26.8	47.0	70.0	105.0	97.8	7.9	1
HRS 400-14		15.0												
HRS 400-16		17.0												
HRS 500-12	500	13.0	32.0	39.0	23.0	56.0	75.0	33.8	47.0	70.0	109.0	113.3	8.9	1
HRS 500-14		15.0												
HRS 500-16		17.0												

HIGH VOLTAGE 90° ELECTRICAL TERMINALS LONG BARREL TWO HOLES (HRL TYPE, ท้ายปลากล่องสองบิตงอ 90°)



Suitable for use with cable size from
10-500 SQ.MM. in right angle position



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]													Q'TY in box
		d2ø	d1ø	Dø	A	B	C	E	F	H	L	M	N	T	
HRL 10-6	10	6.4	4.5	6.2	9.5	12.0	15.8	21.5	7.4	16.5	41.8	48.0	29.5	1.1	100
HRL 10-8		8.4													
HRL 16-6	16	6.4	5.4	7.1	9.5	12.0	15.8	25.0	7.4	16.5	41.8	48.9	33.0	1.2	100
HRL 16-8		8.4													
HRL 25-6	25	6.4	6.8	8.8	11.5	15.0	15.8	28.5	7.4	18.5	45.8	54.6	36.7	1.6	100
HRL 25-8		8.4													
HRL 25-10		10.5													
HRL 35-6	35	6.4	8.2	10.6	11.5	17.0	19.0	32.0	8.0	21.5	52.0	62.6	41.0	2.0	50
HRL 35-8		8.4													
HRL 35-10		10.5													
HRL 50-8	50	8.4	9.5	12.4	11.5	19.0	22.7	35.0	10.9	21.5	55.7	68.1	47.2	2.5	40
HRL 50-10		10.5													
HRL 50-12		13.0													
HRL 70-8	70	8.4	11.2	14.7	11.5	21.0	22.7	35.0	10.9	23.5	57.7	72.4	47.7	3.5	40
HRL 70-10		10.5													
HRL 70-12		13.0													
HRL 95-8	95	8.4	13.5	17.4	13.5	25.5	44.4	38.0	15.8	27.5	85.4	102.8	55.6	3.6	20
HRL 95-10		10.5													
HRL 95-12		13.0													
HRL 120-10	120	10.5	15.0	19.4	14.5	28.0	44.4	40.0	18.8	28.5	87.4	106.8	61.0	4.3	10
HRL 120-12		13.0													
HRL 120-14		15.0													
HRL 150-12	150	13.0	16.5	21.2	16.5	30.5	44.4	50.0	19.8	30.5	91.4	112.6	72.1	4.5	10
HRL 150-14		15.0													
HRL 150-16		17.0													
HRL 185-12	185	13.0	18.5	23.5	16.5	34.0	44.4	50.0	19.8	30.5	91.4	114.9	72.2	4.8	4
HRL 185-14		15.0													
HRL 185-16		17.0													
HRL 240-12	240	13.0	21.5	27.0	16.5	39.5	44.4	56.0	24.8	35.5	96.4	123.4	83.6	5.5	4
HRL 240-14		15.0													
HRL 240-16		17.0													
HRL 300-12	300	13.0	23.5	30.0	16.5	43.5	44.4	67.0	26.8	40.5	101.4	131.4	97.0	6.3	2
HRL 300-14		15.0													
HRL 300-16		17.0													
HRL 400-12	400	13.0	27.0	35.0	16.5	50.8	44.4	67.0	26.8	40.5	101.4	136.4	97.8	7.9	1
HRL 400-14		15.0													
HRL 400-16		17.0													
HRL 500-12	500	13.0	30.0	39.0	16.5	56.0	44.4	75.0	33.8	40.5	101.4	140.4	113.3	8.9	1
HRL 500-14		15.0													
HRL 500-16		17.0													

HIGH VOLTAGE ELECTRICAL SPlice LONG BARREL (HTSL TYPE, สลัฟต่อสายแรงสูง)

Permitted crimp in larger size to assure a strong full tension and high conductive, suitable to connect cable size from 10-500 SQ.MM. 12-35 KV.



Item No.	TIS Wire Size mm ²	DIMENSIONS [MM.]			Q'TY in box
		d1ø	Dø	L	
HTSL 10	10	4.5	6.2	48.0	100
HTSL 16	16	5.4	7.1	55.0	100
HTSL 25	25	6.8	8.8	62.0	100
HTSL 35	35	8.2	10.6	70.0	50
HTSL 50	50	9.5	12.4	75.0	50
HTSL 70	70	11.2	14.7	75.0	40
HTSL 95	95	13.5	17.4	80.0	40
HTSL 120	120	15.0	19.4	85.0	20
HTSL 150	150	16.5	21.2	105.0	20
HTSL 185	185	18.5	23.5	105.0	10
HTSL 240	240	21.5	27.0	118.0	10
HTSL 300	300	23.5	30.0	140.0	10
HTSL 400	400	27.0	35.0	140.0	5
HTSL 500	500	30.0	39.0	155.0	5

ขั้นตอนการย้าสลัฟต่อสาย - ให้ย้าจากในสุดไปปลายสุดแต่ละข้าง



เตรียมหางปลาและสายไฟ



ย้าสายจากด้านใน



ย้าสายที่ปลายสลัฟ



ย้าอีกฝั่งในลักษณะเดียวกัน

UL Underwriters Laboratories Inc.

File #304648 Vol 1 Issued: 2007-05-02
Revised:

FOLLOW-UP SERVICE PROCEDURE (TYPE R)

WIRE CONNECTORS AND SOLDERING LOGS (3007)

Manufacturer: TERMINAL LOGS CO. LTD.
(100096-376) 115/4 MOO 2 KRONOMONT-JONGTHANUM RD
MAHAKAMAT
BANGKOK
BORTYANORI 11130 THAILAND

Applicant: SAME AS MANUFACTURER
(100096-376)

Listee: SAME AS MANUFACTURER
(100096-376)

This Procedure authorizes the above manufacturer to use the marking specified by Underwriters Laboratories Inc. (UL), or any authorized licensee of UL, only on products covered by this Procedure, in accordance with the applicable UL Services Agreement.

The prescribed Mark or Marking shall be used only at the above manufacturing location on such products which comply with this Procedure and any other applicable requirements.

The Procedure contains information for the use of the above named Manufacturer and representatives of Underwriters Laboratories Inc. and is not to be used for any other purpose. It is lent to the Manufacturer with the understanding that it is not to be copied, either wholly or in part, and that it will be returned to Underwriters Laboratories Inc. (UL) or any authorized licensee of UL upon request.

This PROCEDURE, and any subsequent revision, is the property of Underwriters Laboratories Inc. (UL) and the authorized licensee of UL and is not transferable.

Underwriters Laboratories Inc.

Stephen Hewson
Stephen Hewson
Senior Vice President
Global Follow-up Service Operations

William R. Carney
William R. Carney
Director
North American Certification Program

AN INDEPENDENT ORGANIZATION WORKING FOR A SAFER WORLD WITH INTEGRITY, DEDICATION AND KNOWLEDGE

RATINGS AND CRIMP TOOL INFORMATION ;

Pressure Wire Connector	CU.Wire Size			Crimp Tool details			No.of Crimps	Wire strip length mm.
	TIS	AWG	Din mm ²	Model	Die	No.		
CL 10-6,8	10	8	10	FIRST	HD-25X	10	1	8
CL 16-6,8	16	6	16	KUDOS	UB-412	CU-16	1	10
CL 25-6,8,10	25	4	25	KUDOS	UB-412	CU-25	1	10
CL 35-6,8,10,12	35	2	35	KUDOS	UB-412	CU-35	1	10
CL 50-8,10,12	50	1/0	50	KUDOS	UB-412	CU-50	1	14
CL 70-8,10,12	70	2/0	70	KUDOS	UB-412	CU-70	1	16
CL 95-10,12	95	4/0	95	KUDOS	UB-412	CU-95	1	18
CL 120-10,12,14,16	120	250 kcmil	120	KUDOS	UB-412	CU-120	1	20
CL 150-10,12,14,16	150	300 kcmil	150	KUDOS	UB-412	CU-150	1	23
CL 185-12,14,16	185	350 kcmil	185	KUDOS	UB-412	CU-185	2	30
CL 240-12,14,16	240	500 kcmil	240	KUDOS	UB-412	CU-240	2	35
CL 300-12,14,16,18	300	600 kcmil	300	KUDOS	UB-412	CU-300	2	38
CL 400-16,20	400	800 kcmil	400	KUDOS	UB-412	CU-400	2	44
CL 500-16,20	500	1000 kcmil	500	KUDOS	HYCP 630 HE	500	2	47

ELECTRICAL TERMINALS

WIRE-NUT CONNECTORS



BUTT SPLICES



BULLET TERMINALS



CORD - END SLEEVES



INSULATED RING TERMINALS



บริษัท ไทยอิเล็กทรอนิกส์ จำกัด

114 ถนนบางขุนเทียน แขวงบางบอน

เขตบางบอน กรุงเทพมหานคร 10150

TEL : 02-899-7979 , 02-899-7725

E-Mail : thaielectricworks999@gmail.com

Website : <http://www.thai-electricworks.com>

Line id : [thaielectricworks](https://www.thai-electricworks.com)